



## Politex Varnish Glossy

### TECHNICAL DATA SHEET

#### PRODUCT DESCRIPTION

Alkyd resin based, transparent, glossy wood varnish.

#### PRODUCT FEATURES

- Transparent
- Highly resistant to water and abrasion.
- Its micro porous structure allows wood to breath.
- It maintains all the natural beauty of woodwork
- It does not require wiping off after application
- It forms a film layer on the surface.

#### RECOMMENDED FOR

Used for decorative purposes on all interior and exterior wooden surfaces.

#### TECHNICAL SPECIFICATIONS

##### Drying time

Touch dry	1-3	h
Recoat	12	h
Full dry	12	h

\* The provided drying time data are available in 23 °C ambient temperature and 50 ± 2 % relative humidity conditions.

#### SURFACE

Oil and dust on wooden surfaces are thoroughly cleaned. Knots are cleaned and sanded.



## Politex Varnish Glossy

### TECHNICAL DATA SHEET

#### APPLICATION

Apply in two coats. Re-coatable in 12 hours

Application Temperature : min +5 °C / max + 30 °C

Flash off (room temperature, min) : It is ready for use , nothinning required

Coverage (m2/L) : 8-12 (For single coat) Actual coverage may vary depending on the absorbance of substrate.

#### Application Equipment

Brush Applicable  
Roller Applicable

Sponge Applicable

#### TS CLASSIFICATION

#### POZ No.

#### STORAGE and PACKAGING

Packaging 0.75 L 2.5 L 15 L

Storage Conditions In sealed packaging, store in a cool place.

Shelf life 3 years

#### HEALTH AND SAFETY INFORMATION

Refer to the instructions specified in the harmfulness and precautionary statements on the product packaging.

Product of the safety data sheet should be treated by the rules.

Refer to the nearest health facility for unexpected health problems.

#### LEGAL NOTES

All the information and guidelines given in this technical bulletin was formed and developed through the experience in the laboratories of PB, and was systematically collected by our field engineers. "Polisan Boya" has the right to make changes in the product where necessary, without notice. The information given above is valid for the product from the date of publication. It is the user's responsibility to verify the accuracy of the information. The product should be used based on the technical information form for the recommended purpose. It is the responsibility of the users to implement all measures for the fulfilment of the specified requirements. The data in the technical information form is designed to give descriptions of the product performance, under specific test conditions. An important factor in product performance is the variables that may occur in the initial process which should be used as a general guide to the user. Any unauthorised use of this product not covered in the written guidelines, PB will not be held legally responsible. It is always the responsibility of the user to take all necessary precautions regarding specific requirements of the law set out in local and national legislation. Follow the rules of the safety information provided in the Safety Data Sheet regarding operating procedure of the product, protective equipment, storage, fire and first aid etc. Conditions regarding the use of this product after its end date has no warranty. We can not accept responsibility for products past their expiry date. Responsibility can not be accepted.

Please contact the Technical Service department for more detailed information about the product.