

Multi Primer

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Special resin-based, synthetic primers.

PRODUCT FEATURES

- Excellent adhesion
- Creates a smooth and durable layer under topcoat paint
- Metal surfaces are applied with corrosion preventive properties

RECOMMENDED FOR

Indoor and outdoor iron, steel, aluminum, zinc (galvanized surfaces), hard PVC, copper, wood, hardboard, ceramic, glass or many different surfaces such as plaster of used in coatings.

TECHNICAL SPECIFICATIONS

Drying time

Touch dry	2-3	h
Recoat	6-8	h
Full dry	8-9	h

* The provided drying time data are available in 23 °C ambient temperature and 50 ± 2 % relative humidity conditions.

SURFACE

Wooden surfaces

On wooden surfaces; The knots are cleaned, any old paint is scraped off, sanded. Surfaces that need repair; It is puttyed with SUPER PASTE and then sanded.

Iron and Steel Surfaces

Dirt, rust and oil should be removed from surfaces. It can be applied as one or two coats. Old paints should be scraped off the surfaces and sand papered.

Zinc (galvanized surfaces), hard PVC, aluminum, copper surfaces

PVC surfaces before application should be sanded. The other surfaces depend on the surfaces condition should be sanded. Afterwards dust, dirt and oil should be removed from surfaces. Application for Out door zinc surfaces propose 2 coats Multi Astar .

Multi Primer

TECHNICAL DATA SHEET

APPLICATION

It can be applied one or two coats. You should wait 6-8 hours between coats. Use Synthetic Thinner as thinner

Application Temperature	: min +5 °C / max + 30 °C
Thinning Ratio (%)	: For Brush&Roller 5-10%, Spray 10-15%
Consumption (m ² / L)	: 13-15 (For single coat)

Application Equipment

Brush	Applicable
Roller	Applicable
Spray	Applicable

TS CLASSIFICATION

TS 11651 is suitable and has the TSE.

POZ No.

Select Item no. Item number if you do not hide the line by right-clicking.

STORAGE and PACKAGING

Packaging	0.75 L 2.5 L
Storage Conditions	Should be stored in closed packs without being exposed to direct sunlight. The ambient temperature while storage should be between 5-35 °C. Keep packs closed when not in use. Preserve against freezing.
Shelf life	3 years

HEALTH AND SAFETY INFORMATION

Refer to the instructions specified in the harmfulness and precautionary statements on the product packaging.
Product of the safety data sheet should be treated by the rules.
Refer to the nearest health facility for unexpected health problems.

LEGAL NOTES

All the information and guidelines given in this technical bulletin was formed and developed through the experience in the laboratories of PB, and was systematically collected by our field engineers. "Polisan Boya" has the right to make changes in the product where necessary, without notice. The information given above is valid for the product from the date of publication. It is the user's responsibility to verify the accuracy of the information. The product should be used based on the technical information form for the recommended purpose. It is the responsibility of the users to implement all measures for the fulfilment of the specified requirements. The data in the technical information form is designed to give descriptions of the product performance, under specific test conditions. An important factor in product performance is the variables that may occur in the initial process which should be used as a general guide to the user. Any unauthorised use of this product not covered in the written guidelines, PB will not be held legally responsible. It is always the responsibility of the user to take all necessary precautions regarding specific requirements of the law set out in local and national legislation. Follow the rules of the safety information provided in the Safety Data Sheet regarding operating procedure of the product, protective equipment, storage, fire and first aid etc. Conditions regarding the use of this product after its end date has no warranty. We can not accept responsibility for products past their expiry date. Responsibility can not be accepted.

Please contact the Technical Service department for more detailed information about the product.