

Pearl

Product Description: A premium, water-based decorative topcoat for interiors, featuring pure acrylic binder, shimmering pearl additives, and a lustrous finish.

Features: Silkcoat Pearl delivers a pearlescent texture with line or wave patterns, providing excellent coverage. It's washable, water-based, and safe both for people and the environment.

Application Areas: Perfect for properly prepped interior surfaces including previously painted walls, concrete, plaster, black mortar, betopan, glass textile, and paintable wallpaper.

Technical Data:

Composition: Pure Acrylic

Coverage: One coat: 2- 3 m² per kg

Thinner: Water

Solids Content: 69%±2

Thinning Ratio: Apply without thinning. If necessary, maximum 10%

Drying Time: Touch-dry in 25–30 min; Dust-free in 1 hour; Fully cured in 24 hours

pH (25°C): 8–9

Application: The surface to be coated must be free of all dust, dirt, and grease. For old, blistered, or previously painted surfaces, lightly sand the entire area to achieve a clean, dry, and sound base. If needed, repair any imperfections or cracks with Silkcoat Interior Acrylic Putty. For new or absorbent surfaces, use Silkcoat Izolac; for old, dirty, or synthetic painted surfaces, use Silkcoat Universal Primer; and for puttied surfaces, use Silkcoat Putty Primer. Apply Silkcoat Pearl in a single layer, undiluted, using a glass trowel. Use the trowel to create either linear or wave patterns as desired. Clean all tools with water immediately after use. On newly plastered surfaces, wait at least 28 days before painting. Stir the paint thoroughly until fully blended before use. During application and drying, make sure the ambient and surface temperature is between +5°C and +35°C. If working on very glossy or glass-like surfaces, sand the area first to ensure proper adhesion.

Cautions:

S2: Keep out of reach of children.

S24/25: Avoid contact with eyes and skin.

S46: If swallowed, seek medical advice immediately and show the container or label.

Store the product in a tightly sealed container.

Do not pour into the sewage system.

Storage:

Can be kept for at least one year in a cool, clean, and dry place, away from direct sunlight, as long as the container remains unopened.

Packaging:

Plastic buckets: 10 kg, 3 kg, 1 kg.