

SILKCOAT®

'art of paint'

Document Type	Technical Data Sheet (TDS)
Product Name	Palace
Product Description	Palace is an interior decorative paint with a pure acrylic emulsion base, enriched with pearlescent additives for a textured, shimmering effect.
Features	With its pearlescent and matte finish, Palace delivers a unique textured look and enables a variety of design applications. Its water-based, sandy texture and metallic appearance This gives your walls a cool, majestic appearance thanks to its metallic finish.
Application Surfaces	Can be applied to all painted surfaces, concrete, plaster, black plaster, fiber cement panels, glass-textured surfaces, and paintable wallpaper for interior use.
Technical Specifications	Density: 1.31 ± 0.02 (g/ml) Coverage: 3-4 (m²/l), 250-350 (g/m²) Solids Content: 60% ± 2 Dilution: Ready to use, no thinning required. Drying Time: Touch dry in 15–20 min; Dust free in 1 hour; Fully cured in 24 hours
Application	The application surface should be free of dust, dirt, and grease. Any blistered or old paint should be lightly sanded to create a clean, dry, and stable surface. If needed, repair imperfections and cracks using Silkcoat Interior Acrylic Putty. If the surface has been smoothed with plaster, apply Silkcoat Izolac before using Silkomatt. For old, dirty, or synthetic painted surfaces, use Silkcoat Universal Primer; for surfaces where putty has been applied, use Silkcoat Putty Primer. Apply Silkomatt as a single final coat in the same color as Palace. For desired patterns, use a brush to apply Silkcoat Palace in the selected design. As the product starts to dry, gently press a clean, thick brush onto the sanded surface to remove excess liquid. This will give the sand a matte finish while the background remains glossy. Clean tools immediately after use. Thoroughly mix the paint until completely homogeneous before application. During application and drying, ensure the ambient and surface temperature is between +5°C and +35°C. For very glossy or glassy surfaces, prep the surface first to ensure proper adhesion.
Warning	S2: Keep out of reach of children. S24/25: Avoid contact with eyes and skin. S46: If swallowed, seek medical attention immediately; show the container or label. Store tightly sealed in its container. Do not pour into the sewer.
Storage	Store the product in a cool, clean, dry place, away from direct sunlight and with the cabinet door closed. Shelf life is at least 2 years.
Packing	Available in 10 kg and 3 kg PE buckets.

Silkcoat Duvar Kaplamaları San. Ve Tic. Ltd. Şti.

Kaleiçi Neighborhood, Gökçeali Avenue No:63,
Çatalca, İstanbul, Phone: +90 212 789 56 43 /
info@silkcoat.com www.silkcoat.com