

## Velvetto

**Product Description:** Velvetto is part of the Silkcoat Effects collection—a lively, dynamic series featuring a shimmering mother-of-pearl touch, velvety textures, and a glossy look. Made from pure acrylic, it's designed to create fun and vibrant spaces.

**Features:** Thanks to its pearlescent formula, Velvetto delivers a unique semi-gloss, satin-like finish that resembles velvet and allows for a variety of decorative patterns. Its water-based structure is safe for people and the environment.

**Areas of Use:** Can be applied to interior surfaces with proper prep, including previously painted walls, concrete, plaster, roughcast, betopan, glass textile, and paintable wallpaper.

### Technical Specifications:

Density: 1.16± 0.02 (g / ml)

Covers: 3.5-4 (m<sup>2</sup> / lt), 250-350 (g/m<sup>2</sup>)

Dilution Ratio: Ready to use.

Drying Time: Touch dry in 30-45 minutes; Dust-free after 1 hour; Fully cured in 24 hours

### Surface Preparation:

- Before application, make sure the surface is free from all dust, dirt, and grease, and remove any loose or peeling old paint to create a clean, dry, and solid base.
- If the surface isn't smooth, use Silkcoat Interior Acrylic Putty to achieve an even and flawless finish for Silkomat application.
- For surfaces leveled with plaster, apply Silkcoat Izolac before Silkomat; for smooth but old, dirty, or synthetic painted surfaces, use Silkcoat Universal Primer; for surfaces treated with putty, use Silkcoat Putty Primer.
- Apply a single coat of Silkomat in the same color as a primer layer.

## Application:

Before starting, make sure the surface is completely free from dust, dirt, and grease. Sand all areas with peeling or old paint lightly to achieve a clean, dry, and sturdy surface. If needed, repair any imperfections or cracks using Silkcoat Interior Acrylic Putty. For surfaces leveled with plaster, apply Silkcoat Izolac before using Silkomatt. On old, dirty, or synthetic painted surfaces, use Silkcoat Universal Primer; for puttied surfaces, apply Silkcoat Putty Primer. Finish with a single coat of Silkomatt in the Velveto shade. Apply Velveto to the surface with a roller, then—before drying—use a special trowel to create circular patterns. Allow the surface to dry for 4-6 hours depending on weather conditions. Once the first coat has dried, apply the second coat of Velveto with a decorative trowel or roller to form a thin layer, then immediately use circular motions with the special trowel to add texture. Clean all tools with water as soon as you finish. Stir the paint thoroughly until it's fully homogeneous before use. During application and drying time, keep the room and surface temperature between +5°C and +35°C. For very glossy or glass-like surfaces, sand first to ensure proper adhesion and a solid base.

## Warnings:

S2: Keep out of reach of children.

S24/25: Avoid contact with eyes and skin.

S46: If swallowed, seek medical advice immediately and show the container or label.

Store the product in a tightly sealed container.

Do not pour into the sewage system.

**Storage:** Keep in a cool, clean, and dry place, away from direct sunlight, with the container sealed.

Can be stored for at least 1 year.

**Packaging:** Plastic buckets,  
available in 10 kg and 3 kg sizes.